



CellD Systems

	CellD 20	CellD 40	CellD 100		CellD 125 (EVO)
	DPS 850B-48-2	DPS 850B-48-3	DPS 850B-48-6	DPS 2900B-48-3	DPS 2900B-48-3
					
	<i>EnergE</i>	<i>EnergE</i>	<i>EnergE</i>	<i>EnergE</i>	<i>EnergE</i>
Rectifier module	DPR 850B-48 (max. 2 pcs.)	DPR 850B-48 (max. 3 pcs.)	DPR 850B-48 (max. 6 pcs.)	DPR 2900B-48 (max. 3 pcs.)	DPR 2900B-48 (max. 3 pcs.)
Efficiency	95,2%	95.2%	95.2%	96.4% or 97,2%	96.4% or 97,2%
Install power (max. config.)	1,7 kW	2.55 kW	5.1 kW	8.7 kW	8.7 kW
Dimensions H x W x D	43.6 (1U) x 484.3 (19') x 280 mm	43.6 (1U) x 484.3 (19') x 280 mm	86.8 (2U) x 484.3 (19') x 295 mm	86.8 (2U) x 484.3 (19') x 323 mm	133.5 (3U) x 481.5 (19') x 329 mm
Weight	4.0 kg	4.1 kg	7.0 kg	7.0 kg	15 kg
Input voltage range	80 - 300 V _{RMS}	80 - 300 V _{RMS}	80 - 300 V _{RMS}	80 - 300 V _{RMS}	80 - 300 V _{RMS}
Max. output current / max. installed power	26 A / 1,7 kW	40 A / 2.55 kW	100 A / 5.1 kW	100 A / 8.7 kW	125 A / 8.7 kW
Controller	ORION				
Local interface	Display, keypad, LEDs				
Remote monitoring	Alarm relays, modem option, LAN, SNMP protocol				

Delta confidential