

Charger box “L”

Back to: [1~3kVA / 5~10kVA](#)
[3ph monoblock](#) / [3ph modular](#)

PN: CHG252C2D1000-N

SAP NAME: F CHARGE FOR 16/20PCS BATTERY NO CHARGER

Description: 19" empty charger box for all external charger boards for RT application. Max 2 charger boards in one charger box.



MODEL	CHG-240V- 4,5A-1	CHG-240V- 4,5A-2	CHG-192V- 4,5A-1	CHG-192V- 4,5A-2
INPUT				
Voltage	170~290 Vac (Full load)			
Frequency	40~70 Hz			
Current	< 8 A			
Power Factor	> 0,97			
Protection	12 A fuse per charger board			
OUTPUT				
Output Power	1125W ±225W	2250W ±450W	900W ±180W	1800W ±360W
Charger Voltage	240V~272V		192V~217,6V	
Charger Current	4,5 A	9 A	4,5 A	9 A
Protection	8 A fuse per charger board			
PHYSICAL				
Dimensions (W x D x H)	384 x 440 x 88,5 mm (terminal block included) 384 x 440 x 88,5 mm (terminal block excluded)			
Weight	4 kg			

Applicable to UPS:

- RT-series 5/6kVA.
- RT-series 10kVA.
- For connection from charger box to RT battery cabinet a Delta battery cable ([3080121702-S94](#)) with one open end can be used.
- EH-series.
- HPH, NH+,DPS,DPH-series (2 charger boxes in serial connection or UPS charging system).

